

Digital vacuum measuring instrument

testo 552 - For the evacuation of refrigeration/air conditioning systems and heat pumps

Highly accurate and reliable measurement results

Maintenance-free absolute pressure sensor

2400 hours' battery life (100 days' continuous operation)

Measurement of evaporation temperature H_oO

Optical alarm when limit values are exceeded

Extremely robust and resistant to water and dirt (IP42)



The testo 552 is a digital vacuum measuring instrument for the evacuation of refrigeration systems and heat pumps. It measures even the smallest absolute pressures and provides highly precise information on the status of the dehumidification of a system (removal of foreign substances, incl. oils or foreign gases).

The testo 552 is the only digital vacuum measuring instrument whose absolute pressure sensor, in contrast to other sensor technologies, no longer needs to be serviced, and still provides highly accurate measurement results. Thanks to the battery life of up to 2400 hours with two conventional AA batteries, you can use the testo 552 in continuous operation for 100 days without changing the battery. Its robust construction makes it suitable for daily use, and protects from dirt and water.



Absolute pressure sensor

0 to 1,000 micron: up to ± 10 micron

0 to 150,000 micron: $\pm 0.3\%$ FS = ± 0.6 hPa

150,000 to 825,080 micron: $\pm 0.3\%$ FS =

absolute: 6 bar / 87 psi (relative: 5 bar / 72 psi)

1.100 to 0 mbar /

0 to 200 hPa /

±3.3 hPa

200 to 1,100 hPa /

0.01 hPa / 10 micron

825,080 to 0 micron 0 to 1,33 hPa /

Technical data

testo 552

Vacuum measuring instrument with maintenance-free sensor for efficient evacuation





General technical data

Sensor type

Measuring range

Accuracy vacuum

±1 digit (at +22 °C, trust level

Resolution vacuum

Overload vacuum

vacuum

95%)

ac	delierar teciniicar data		
Sto	rage temperature	-20 to +50 °C	
Оре	erating temperature	-20 to +50 °C	
Dim	nensions	250 x 165 x 55 mm	
Wei	ght	Approx. 500 g	
Pro	tection class	IP42	
Bat	tery type	2 AA batteries	
Bat	tery life	2.400 h (approx. 130 h with backlighting activated)	
Cor	nnection	- 2 x 7/16" UNF - 1 x MiniDIN (connection to testo 570)	
Sen	isor	Absolute pressure sensor	
Para	ameter	mmHg, Torr, mbar, hPa, micron, inH ₂ 0, inHg, Pa	
Mea	asuring rate	0.5 s	
War	rranty	2 years	

Accessories

Part no.

-			
	MiniDIN connection cable for connecting testo 552 with the digital manifold testo 570	0554 5520	